

FEATURES

• High tensile strength means it's able to resist abrasion and other forces.

Handles operating

resistance.

temperatures up to 500°F

(260°C) with moderate chemical

- Strong, dense technical fabric with excellent performance.
- Moderate resistance to acids and alkalis.

Spark and fire resistant.

Moderate

resistance to

acids and alkalis.

- specification.
- Quality assurance under the strictest protocols to ASTM standards.

• 100% virgin premium fibers. • Fits any baghouse to

OPTIONS

- Acid Resistant Finish
- Teflon B Finish
- E-PTFE Membrane
- Wear Strips

- Woven Cuff
- Non Woven Cuff
- NFPA Wire

APPLICATIONS

- Cement
- Chemicals
- Foundry
- Power Plants
- Waste to Energy
- Pharmaceuticals

- Carbon Black
- Aggregates
- Metals/Steel
- Mining
- Biomass



Supports


applications

with operating

temperatures up to 500°F (260°C). Able to resist

abrasion and other

forces.









FABRIC PROPERTIES

100% Fiberglass

Abrasion Resistance	Good
Acid Resistance	Good
Alkali Resistance	Good
Oxidation Resistance	Excellent
Operating Temperature	500°F (260°C)
Short Surge Temperature	550°F (287°C)
Investment	\$\$



Contact Albarrie's Technical Sales Expert for all your options

PRODUCT GALLERY







Disclaimer: Information provided by Albarrie on this sales sheet ("Sheet") is for general information purposes only. All information on the Sheet is provided in good faith, however Albarrie makes no representation or warranty of any kind, express or implied, regarding the accuracy, adequacy, validity, reliability, availability or completeness of any information on the Sheet. Products may not work as advertised or perform differently based on application, operating conditions, and depend on chemical, thermal, and humidity and other factors.

www.albarrie.com