

INDUSTRIAL AIR FILTRATION

AFFINITY™

FILTER MEDIA

META-ARAMID BAGHOUSE FILTER BAGS

ENHANCE PERFORMANCE

Great mechanical stability in industrial applications with **operating temperatures up to 400°F (204°C)**, offering great mechanical stability.

KEY BENEFITS



LONG SERVICE LIFE

Withstands abrasion in harsh environments.



EXCELLENT HEAT & FIRE RESISTANCE

Resists high heat and combustion.



GOOD MECHANICAL STABILITY

Withstands abrasion and other forces.



HIGH-TEMPERATURE RESISTANCE

Supports applications with operating temperatures up to 400°F (204°C).

FEATURES

- Excellent chemical resistance.
- High tensile strength
- Layer with P84® Polyimide fibers in Albarrie's **Tandem™** filter bags.
- Non-flammable fibers.
- 100% virgin premium fibers.
- Fits any baghouse to specification.
- Quality assurance under the strictest protocols to ASTM standards.

OPTIONS

- Fire Retardant
- Water-Repellent Treatment
- Oil Repellent Treatment
- PTFE Finish
- E-PTFE Membrane
- Singed
- Scrim Supported
- Wear Strips
- Non-Woven Cuff
- Woven Cuff
- NFPA Wire
- Micro Denier

APPLICATIONS

- Asphalt
- Aggregates
- Cement
- Chemicals
- Metals
- Mining



FABRIC PROPERTIES

	100% Meta Aramid	Micro Denier Meta Aramid	Meta Aramid + P84® (Tandem™)
Abrasion Resistance	Excellent	Excellent	Excellent
Acid Resistance	Good	Good	Good
Alkali Resistance	Very Good	Very Good	Very Good
Oxidation Resistance	Good	Good	Good
Operating Temperature	400°F (204°C)	400°F (204°C)	400°F (204°C)
Surge Temperature	430°F (221°C)	430°F (221°C)	430°F (221°C)
Investment	\$\$	\$\$\$	\$\$\$\$

Contact Albarrie's Technical Sales Expert for all your options

PRODUCT GALLERY



Disclaimer: Information provided by Albarrie on this sales sheet ("Sheet") is for general information purposes only. All information on the Sheet is provided in good faith, however Albarrie makes no representation or warranty of any kind, express or implied, regarding the accuracy, adequacy, validity, reliability, availability or completeness of any information on the Sheet. Products may not work as advertised or perform differently based on application, operating conditions, and depend on chemical, thermal, and humidity and other factors.

